ALDON Company, Inc.

STATE OF THE PARTY OF THE PARTY

3410 Sunset Avenue, Waukegan, Illinois 60087 TEL: 847-623-8800 FAX: 847-623-6139 e-rail@aldonco.com --- www.aldonco.com

| Company | | | Date | | |
|---|--|---|--|---|--|
| Contact | | | PO Number | | |
| Phone | | Fax | | | |
| Permanent Rerailer Sizing Form | | | | | |
| Dear Customer: We need the following information to process your order. | | | | | |
| 1 | Height of Rail Above the Tie | | | | |
| • | 1 9 | † | "A" Overall height from top of tie | | |
| | Ä | B | "B" Height of rail from top of tie plate | | |
| | | | "C" Thickness of tie plate | | |
| 2 | Rail size and Section (look for markings on web of rail: 100RE, 9020, etc.) | | | | |
| 3 | Clearance Above Rail The central panel diamond stands 2" above the top of the rail. Will this interfere with any locomotive, car shunter, snow plow, or other rolling stock? Yes No If yes, indicate minimum clearance you need above top of rail. | | | | |
| 4 | | | | | |
| 5 | Style of Rerailer Check which style | WHEEL LOAD 20 Ton/Wheel (freight cars) CAPACITY: 40 Ton/Wheel (steel mill ladle cars) | | | |
| | Note: HALF/FULL DIAMOND RERAILERS ARE NOT PAINTED YELLOW. (All Diamond Rerailers are manufactured and shipped in raw steel.) | 4018-10 Full Diamond 20 ton/wheel 4018-22 Full Diamond 40 ton/wheel | | 4018-11 Half Diamond 20 ton/wheel 4018-23 Half Diamond 40 ton/wheel | |